



FRONIUS PRIMO GEN24 PLUS

The flexible storage inverter
with need-based back-up power options

PRELIMINARY DATA



Integrated Data
Communication



Dynamic Peak
Manager



Multi Flow
Technology



SuperFlex
Design



Back-up power



PV Point



The Fronius Primo GEN24 Plus in power categories from 3.0 to 6.0 kW is the ideal hybrid inverter for private households. With various features included as standard it fulfills every customer's needs.

PRELIMINARY TECHNICAL DATA FRONIUS PRIMO GEN24 PLUS (3.0, 3.6, 4.0, 4.6, 5.0, 6.0)

INPUT DATA	PRIMO GEN24 3.0 PLUS	PRIMO GEN24 3.6 PLUS	PRIMO GEN24 4.0 PLUS	PRIMO GEN24 4.6 PLUS	PRIMO GEN24 5.0 PLUS	PRIMO GEN24 6.0 PLUS
Number of MPP trackers	2					
Max. input current ($I_{dc\ max\ MPPT1 / MPPT2}$)	22 A / 12 A					
Max. array short circuit current (MPPT1/MPPT2)	33 A / 18 A					
DC input voltage range ($U_{dc\ min} - U_{dc\ max}$)	65 V - 600 V					
Nominal input voltage ($U_{dc,r}$)	350 V					
Feed-in start voltage ($U_{dc\ start}$)	80 V					
Usable MPP voltage range	65 V - 530 V					
Number of DC connections (MPPT1 / MPPT2)	2 / 2					
Max. PV generator output ($P_{dc\ max}$)	4,5 kW _{peak}	5,5 kW _{peak}	6,0 kW _{peak}	6,9 kW _{peak}	7,5 kW _{peak}	9,0 kW _{peak}

OUTPUT DATA	PRIMO GEN24 3.0 PLUS	PRIMO GEN24 3.6 PLUS	PRIMO GEN24 4.0 PLUS	PRIMO GEN24 4.6 PLUS	PRIMO GEN24 5.0 PLUS	PRIMO GEN24 6.0 PLUS
AC nominal output ($P_{ac,r}$)	3000 W	3680 W	4000 W	4600 W	5000 W	6000 W
Max. output power	3000 VA	3680 VA	4000 VA	4600 VA	5000 VA	6000 VA
Max. output current ($I_{ac\ max}$)	20,00 A	24,53 A	26,67 A	27,50 A	27,50 A	27,50 A
Grid connection (voltage range)	1-NPE 220 V / 230 V (150 V - 270 V)					
Frequency (frequency range)	50 Hz / 60 Hz (45 Hz - 65 Hz)					
Total harmonic distortion	< 3,5 %					
Power factor ($\cos\ \phi_{ac,r}$)	0,8 - 1 ind. / cap.					
Back-up power	1-NPE 220 V / 230 V					

OUTPUT DATA PV POINT	PRIMO GEN24 3.0 PLUS	PRIMO GEN24 3.6 PLUS	PRIMO GEN24 4.0 PLUS	PRIMO GEN24 4.6 PLUS	PRIMO GEN24 5.0 PLUS	PRIMO GEN24 6.0 PLUS
Max. output power	3680 VA					
Max. output current ($I_{ac\ max}$)	16 A					
Grid connection (voltage range)	1 - NPE 220 V / 230 V					
Frequency (frequency range)	50 Hz / 60 Hz					
Switchover time	< 5 seconds					
Power factor ($\cos\ \phi_{ac,r}$)	0,8 - 1 ind. / cap.					

BATTERY CONNECTION	PRIMO GEN24 3.0 PLUS	PRIMO GEN24 3.6 PLUS	PRIMO GEN24 4.0 PLUS	PRIMO GEN24 4.6 PLUS	PRIMO GEN24 5.0 PLUS	PRIMO GEN24 6.0 PLUS
Number of DC connections	1					
Max. input current ($I_{dc\ max}$)	22 A					
DC input voltage range ($U_{dc\ min} - U_{dc\ max}$)	150 V - 530 V					
Max. input / output power ¹⁾	3170 W	3890 W	4230 W	4860 W	5290 W	6340 W
Max. AC charging power	3000 W	3680 W	4000 W	4600 W	5000 W	6000 W

PRELIMINARY TECHNICAL DATA FRONIUS PRIMO GEN24 PLUS (3.0, 3.6, 4.0, 4.6, 5.0, 6.0)

GENERAL DATA	PRIMO GEN24 3.0 PLUS	PRIMO GEN24 3.6 PLUS	PRIMO GEN24 4.0 PLUS	PRIMO GEN24 4.6 PLUS	PRIMO GEN24 5.0 PLUS	PRIMO GEN24 6.0 PLUS
Dimensions (height x width x depth)	528 x 474 x 164 mm					
Weight (inverter / with packaging)	16,6 / 19,2 kg					
Degree of protection	IP 66					
Protection class	1					
Overvoltage category (DC/AC) ²⁾	2 / 3					
Inverter design	Transformerless					
Cooling	Regulated air cooling					
Installation	Indoor and outdoor installation					
Ambient temperature range	-40 - +60 °C					
Permitted humidity	0 - 100 %					
Max. altitude	4.000 m					
DC PV connection technology	4x DC+ and 4x DC- screw terminals 2,5 - 10 mm ²					
DC battery connection technology	1x BATT+ and 1x BATT- push-in screw terminals 2,5 - 10 mm ²					
AC connection technology	3 pole AC push-in screw terminals 2,5 - 10 mm ² 5x PE screw terminals 2,5 - 16 mm ²					
Certificates and compliance with standards	certificates pending					
Back-up power functions	PV Point, back-up power ¹⁾					
Compatible batteries	BYD Battery-Box HV, LG CHEM RESU7H / RESU10H ³⁾					

EFFICIENCY	PRIMO GEN24 3.0 PLUS	PRIMO GEN24 3.6 PLUS	PRIMO GEN24 4.0 PLUS	PRIMO GEN24 4.6 PLUS	PRIMO GEN24 5.0 PLUS	PRIMO GEN24 6.0 PLUS
Max. efficiency	97,4 %					
Europ. efficiency (η _{EU})	97,0 %					

PROTECTIVE DEVICES	PRIMO GEN24 3.0 PLUS	PRIMO GEN24 3.6 PLUS	PRIMO GEN24 4.0 PLUS	PRIMO GEN24 4.6 PLUS	PRIMO GEN24 5.0 PLUS	PRIMO GEN24 6.0 PLUS
DC insulation measurement	Yes					
Overload behaviour	Operating point shift. Power limitation					
DC disconnecter	Yes					
Reverse polarity protection	Yes					

INTERFACES	PRIMO GEN24 3.0 PLUS	PRIMO GEN24 3.6 PLUS	PRIMO GEN24 4.0 PLUS	PRIMO GEN24 4.6 PLUS	PRIMO GEN24 5.0 PLUS	PRIMO GEN24 6.0 PLUS
WLAN / 2x Ethernet LAN	Fronius Solar.web, Modbus TCP SunSpec, Fronius Solar API (JSON)					
6 digital in/out	Interface to ripple control receiver, energy management					
USB 2.0 (A-socket)	1 A supply					
Emergency stop (WSD)						
Datalogger and webserver	Included					
2x RS485	Modbus RTU SunSpec or meter connection, SunSpec, Smart Meter					

¹⁾ Depending on the connected battery ²⁾ According to IEC 62109-1 ³⁾ Compatible soon
For further information on the availability of this inverter in your country please see www.fronius.com.

/ Perfect Welding / Solar Energy / Perfect Charging

THREE BUSINESS UNITS, ONE GOAL: TO SET THE STANDARD THROUGH TECHNOLOGICAL ADVANCEMENT.

What began in 1945 as a one-man operation now sets technological standards in the fields of welding technology, photovoltaics and battery charging. Today, the company has around 4,550 employees worldwide and 1,241 patents for product development show the innovative spirit within the company. Sustainable development means for us to implement environmentally relevant and social aspects equally with economic factors. Our goal has remained constant throughout: to be the innovation leader.

Further information about all Fronius products and our global sales partners and representatives can be found at www.fronius.com

v09 May 2018 EN

Fronius India Private Limited
GAT no 312, Nanekarwadi
Chakan, Taluka - Khed District
Pune 410501
India
pv-sales-india@fronius.com
www.fronius.in

Fronius Australia Pty Ltd.
90-92 Lambeck Drive
Tullamarine VIC 3043
Australia
pv-sales-australia@fronius.com
www.fronius.com.au

Fronius UK Limited
Maidstone Road, Kingstons
Milton Keynes, MK10 0BD
United Kingdom
pv-sales-uk@fronius.com
www.fronius.co.uk

Fronius International GmbH
Froniusplatz 1
4600 Wels
Austria
pv-sales@fronius.com
www.fronius.com